



# THE GO-TO GROUT FOR RELIABILITY, VERSATILITY AND PROVEN RESULTS.



The ultimate performance cement grout.


- Uniform consistent color
- No efflorescence
- Stain resistant — No sealer required
- Lightweight for superior handling
- Same coverage as 25 lbs. of traditional sanded grout



# CUSTOM®

TILE INSTALLATION SYSTEMS

# AVAILABLE IN 40 COLORS.



Sample colors shown generally approximate the color of the grout. Final installed color may vary. Please use our color card or grout kit for more accurate color representation.

- Reduces call backs
- No efflorescence
- Color consistent — No shading
- Fast setting. Develops high early strengths. Walkable in just 4 hours
- 17 lbs. (7.71 kg) covers the same area as a typical 25 lb. (11.34 kg) bag
- Meets ANSI A118.7
- For grout joints up to 1/2" (13 mm)
- Polymer-modified cementitious grout

TILE SIZE	JOINT SIZE					
	1/16" (1.6 mm)	1/8" (3.2 mm)	3/16" (4.8 mm)	1/4" (6.3 mm)	3/8" (9.5 mm)	1/2" (12.7 mm)
Width x Length x Thickness						
1" x 1" x 1/4" (2.5 x 2.5 x .64 cm)	96 ft <sup>2</sup> (8.9 m <sup>2</sup> )	54 ft <sup>2</sup> (5 m <sup>2</sup> )	40 ft <sup>2</sup> (3.7 m <sup>2</sup> )	33 ft <sup>2</sup> (3.1 m <sup>2</sup> )	27 ft <sup>2</sup> (2.5 m <sup>2</sup> )	24 ft <sup>2</sup> (2.2 m <sup>2</sup> )
2" x 2" x 1/4" (5 x 5 x .64 cm)	181 ft <sup>2</sup> (16.8 m <sup>2</sup> )	96 ft <sup>2</sup> (8.9 m <sup>2</sup> )	68 ft <sup>2</sup> (6.3 m <sup>2</sup> )	54 ft <sup>2</sup> (5.0 m <sup>2</sup> )	40 ft <sup>2</sup> (3.7 m <sup>2</sup> )	33 ft <sup>2</sup> (3.1 m <sup>2</sup> )
4.25" x 4.25" x 1/4" (10.8 x 10.8 x .64 cm)	372.4 ft <sup>2</sup> (34.6 m <sup>2</sup> )	192 ft <sup>2</sup> (17.8 m <sup>2</sup> )	131 ft <sup>2</sup> (12.2 m <sup>2</sup> )	101 ft <sup>2</sup> (9.4 m <sup>2</sup> )	71 ft <sup>2</sup> (6.6 m <sup>2</sup> )	56 ft <sup>2</sup> (5.2 m <sup>2</sup> )
6" x 6" x 1/4" (15.2 x 15.2 x .64 cm)	521 ft <sup>2</sup> (48.4 m <sup>2</sup> )	266 ft <sup>2</sup> (24.7 m <sup>2</sup> )	181 ft <sup>2</sup> (16.8 m <sup>2</sup> )	139 ft <sup>2</sup> (12.9 m <sup>2</sup> )	96 ft <sup>2</sup> (8.9 m <sup>2</sup> )	75 ft <sup>2</sup> (7.0 m <sup>2</sup> )
12" x 12" x 3/8" (30.5 x 30.5 x 1 cm)	688 ft <sup>2</sup> (63.9 m <sup>2</sup> )	348 ft <sup>2</sup> (32.3 m <sup>2</sup> )	234 ft <sup>2</sup> (21.7 m <sup>2</sup> )	177 ft <sup>2</sup> (16.5 m <sup>2</sup> )	121 ft <sup>2</sup> (11.2 m <sup>2</sup> )	92 ft <sup>2</sup> (8.6 m <sup>2</sup> )
18" x 18" x 3/8" (45.7 x 45.7 x 1 cm)	1028 ft <sup>2</sup> (95.5 m <sup>2</sup> )	518 ft <sup>2</sup> (48.1 m <sup>2</sup> )	348 ft <sup>2</sup> (32.3 m <sup>2</sup> )	262 ft <sup>2</sup> (24.4 m <sup>2</sup> )	177 ft <sup>2</sup> (16.5 m <sup>2</sup> )	135 ft <sup>2</sup> (12.5 m <sup>2</sup> )
6" x 24" x 3/8" (15.2 x 61 x 1 cm)	552 ft <sup>2</sup> (51.3 m <sup>2</sup> )	279 ft <sup>2</sup> (26 m <sup>2</sup> )	189 ft <sup>2</sup> (17.5 m <sup>2</sup> )	143 ft <sup>2</sup> (13.3 m <sup>2</sup> )	98 ft <sup>2</sup> (9.1 m <sup>2</sup> )	75 ft <sup>2</sup> (7 m <sup>2</sup> )
12" x 24" x 3/8" (30.5 x 61 x 1 cm)	915 ft <sup>2</sup> (85 m <sup>2</sup> )	461 ft <sup>2</sup> (42.8 m <sup>2</sup> )	310 ft <sup>2</sup> (28.8 m <sup>2</sup> )	234 ft <sup>2</sup> (21.7 m <sup>2</sup> )	158 ft <sup>2</sup> (14.7 m <sup>2</sup> )	121 ft <sup>2</sup> (11.2 m <sup>2</sup> )

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more tile and joint sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.



Select a qualifying system of Prep, Set and Grout products and CUSTOM will warranty the tile installation for life, including tile, materials and labor. See website for complete details.

©2020 Custom Building Products. All rights reserved. The CUSTOM® logo and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit [custombuildingproducts.com](http://custombuildingproducts.com) for updated technical data sheets and SDS information.

Custom Building Products  
800-272-8786  
[custombuildingproducts.com](http://custombuildingproducts.com)

SS160 3/20R

